



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ ATF PRO +4
Synthetic Automatic Transmission Fluid

Product code : 908720

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline Global
Operations
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address of person : SDS@valvolineglobal.com
responsible for the SDS

1.4 Emergency telephone number

00-800-825-8654, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.

Prevention:

P273 Avoid release to the environment.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Additional Labelling

EUH208 Contains BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS, DODECYL HYDROXYPROPYL SULFIDE, C14-C18 alpha-olefin epoxide, reaction products with boric acid. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- xxxx	Asp. Tox. 1; H304	>= 25 - < 40
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8 265-158-7	Asp. Tox. 1; H304	>= 2.5 - < 5



ValvolineTM
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
ValvolineTM ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

	649-468-00-3 01-2119487077-29-xxxx		
Mineral Oil	Not Assigned 01-2119484627-25-xxxx, 01-2119471299-27-xxxx, 01-2119487077-29-xxxx, 01-2119480132-48-xxxx	Asp. Tox. 1; H304	>= 2.5 - < 5
BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS	Not Assigned	Skin Sens. 1B; H317 specific concentration limit Skin Sens. 1B; H317 > 10 - 100 %	>= 0.5 - < 1
DODECYL HYDROXYPROPYL SULFIDE	67124-09-8 266-582-5 01-2119953277-30-xxxx	Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	>= 0.5 - < 1
C14-C18 alpha-olefin epoxide, reaction products with boric acid	Not Assigned 01-2119976364-28-xxxx	Skin Sens. 1B; H317	>= 0.1 - < 0.5
ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.	61791-44-4 263-177-5	Met. Corr. 1; H290 Acute Tox. 4; H302 Acute Tox. 4; H312 Eye Dam. 1; H318 Aquatic Acute 1; H400 M-Factor (Acute aquatic toxicity): 10	>= 0.025 - < 0.1

For explanation of abbreviations see section 16.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If on skin, rinse well with water.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing : High volume water jet



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

media

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Use personal protective equipment.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Personal protective equipment

- Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Hand protection	
Material	: neoprene, nitrile rubber
Break through time	: >= 240 min
Glove thickness	: >= 0.35 mm
Directive	: Equipment should conform to EN 374
Remarks	: The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the protective glove. The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Respiratory protection	: No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	: liquid
Colour	: red
Odour	: No data available
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 199 °C Method: Cleveland open cup



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	0.0133333 hPa (21.11 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.8508 g/cm ³ (15.56 °C)
Solubility(ies)		
Water solubility	:	negligible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 34 mm ² /s (40 °C)
Oxidizing properties	:	No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat
Heat

10.5 Incompatible materials

Materials to avoid : Alkali metals
alkalis
aluminum
Ammonia
Combustible material
halogens
isocyanates
Lead
Metals
metal oxides
Oxidizing agents
peroxides
reducing agents
sodium
Strong acids
strong bases
water
Zinc
Peroxides

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DODECYL HYDROXYPROPYL SULFIDE:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Acute oral toxicity : LD50 (Rat): > 16,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

Acute oral toxicity : LD50 (Rat): 630 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 0.6 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): Approximate 1,600 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:



Valvoline™
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Assessment : Slight, transient irritation
Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result : Slight, transient irritation

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit
Result : No skin irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Species : Rabbit
Result : Slight, transient irritation

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

Result : Corrosive to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Result : No eye irritation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

DODECYL HYDROXYPROPYL SULFIDE:

Species : Rabbit
Result : No eye irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Species : Rabbit
Result : No eye irritation

ETHANOL, 2,2'-IMINOBI-, N-TALLOW ALKYL DERIVS.:

Result : Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Product:

Remarks : Causes sensitisation.

Components:

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Assessment : The product is a skin sensitiser, sub-category 1B.

DODECYL HYDROXYPROPYL SULFIDE:

Test Type : Local lymph node assay
Species : Guinea pig
Assessment : May cause sensitisation by skin contact.
Method : OECD Test Guideline 429

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Test Type : Buehler Test
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 406



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

Genotoxicity in vitro : Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster ovary cells
Metabolic activation: with and without metabolic activation
Result: Positive results were obtained in some in vitro tests.

Test system: rat hepatocytes
Result: negative

Carcinogenicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Mineral Oil:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Mineral Oil:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Harmful to aquatic life.

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10,000 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

BENZENE, POLYPROPENE DERIVATIVES, SULFONATED, CALCIUM SALTS:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DODECYL HYDROXYPROPYL SULFIDE:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0.75 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 0.58 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae/aquatic plants : EL50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF

M-Factor (Acute aquatic toxicity) : 1

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL: 0.32 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

M-Factor (Chronic aquatic toxicity) : 1

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Chronic aquatic toxicity Category 1; Very toxic to aquatic life with long lasting effects.

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

- Exposure time: 96 h
Test Type: semi-static test
Test substance: WAF
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF
Remarks: No toxicity at the limit of solubility
- Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

- Acute aquatic toxicity : Not classified based on available information.
- Chronic aquatic toxicity : Not classified based on available information.

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 0.11 mg/l
Exposure time: 96 h
Remarks: The toxicological data has been taken from products of similar composition.
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0.011 mg/l
Exposure time: 48 h
Remarks: The toxicological data has been taken from products of similar composition.
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (microalgae)): 0.03 mg/l
End point: Biomass
Exposure time: 96 h
Test Type: static test
Remarks: The toxicological data has been taken from products of similar composition.
- M-Factor (Acute aquatic toxicity) : 10



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Toxicity to fish (Chronic toxicity) : Chronic Toxicity Value: 0.0179 mg/l
Exposure time: 30 d
Species: Danio rerio (zebra fish)
Remarks: The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 0.14 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Remarks: The toxicological data has been taken from products of similar composition.

Ecotoxicology Assessment

Acute aquatic toxicity : Acute aquatic toxicity Category 1; Very toxic to aquatic life.

Chronic aquatic toxicity : Not classified based on available information.

12.2 Persistence and degradability

Components:

DODECYL HYDROXYPROPYL SULFIDE:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 26.7 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

ETHANOL, 2,2'-IMINOBIS-, N-TALLOW ALKYL DERIVS.:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 76 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

12.3 Bioaccumulative potential

Components:

DODECYL HYDROXYPROPYL SULFIDE:



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Partition coefficient: n-octanol/water : log Pow: 4.7 - 6.5

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Partition coefficient: n-octanol/water : log Pow: 9.4

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.2 UN proper shipping name

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.3 Transport hazard class(es)

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA_P : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
RID : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA (Cargo) : Not regulated as a dangerous good
IATA_P (Passenger) : Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable
Control of Major Accident Hazards Regulations 2015 (COMAH)	34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to new and expectant mothers at work contained in Regulation 16 to 18) and of the Pregnant Workers Directive 92/85/EEC.

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

TCSI : Not in compliance with the inventory



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

TSCA	:	All substances listed as active on the TSCA inventory
AIIC	:	Not in compliance with the inventory
DSL	:	All components of this product are on the Canadian DSL
ENCS	:	On the inventory, or in compliance with the inventory
KECI	:	On the inventory, or in compliance with the inventory
PICCS	:	On the inventory, or in compliance with the inventory
IECSC	:	On the inventory, or in compliance with the inventory
NZIoC	:	Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H290	:	May be corrosive to metals.
H302	:	Harmful if swallowed.
H304	:	May be fatal if swallowed and enters airways.
H312	:	Harmful in contact with skin.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H400	:	Very toxic to aquatic life.
H410	:	Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	:	Acute toxicity
Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Met. Corr.	:	Corrosive to metals
Skin Sens.	:	Skin sensitisation



SAFETY DATA SHEET
according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000261489

Classification of the mixture:

Aquatic Chronic 3 H412

Classification procedure:

Based on product data or assessment

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not



Valvoline™
Global

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ ATF PRO +4 Synthetic Automatic
Transmission Fluid

Version: 4.0

Revision Date: 13.10.2023

Print Date: 18/02/2026

to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN