

Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ GEAR OIL 75W80 RPC

Gear Oil

Product code : 867068

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data

Ellis Enterprises B.V., an affiliate of Valvoline

Wieldrechtseweg 39 3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains Di-tert-butyl polysulfide, Reaction products of 4-methyl-2-pentanol



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl. May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8 265-158-7 01-2119487077-29-xxxx	Asp. Tox.1; H304	>= 40,00 - < 50,00
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 2,50 - < 5,00
Di-tert-butyl polysulfide	68937-96-2 273-103-3 01-2119540515-43-xxxx	Skin Sens.1B; H317 Aquatic Chronic3; H412	>= 2,50 - < 5,00
Reaction products of 4- methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert- alkyl	931-384-6 01-2119493620-38-xxxx	Acute Tox.4; H302 Eye Dam.1; H318 Skin Sens.1B; H317 Aquatic Chronic2; H411	>= 0,50 - < 1,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

Valvoline,

Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: If product is heated above its flash point it will produce vapors sufficient to support combustion. Vapors are heavier than air

and may travel along the ground and be ignited by heat, pilot



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Revision Date: 07.04.2020 Print Date: 14/09/2022 Version: 6.0

lights, other flames and ignition sources at locations near the

point of release.

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

: Persons not wearing protective equipment should be excluded Personal precautions

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel, Methods for cleaning up

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

For personal protection see section 8.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

Hygiene measures : General industrial hygiene practice.

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Hand protection

Remarks : Nitrile rubber butyl-rubber

Skin and body protection : Wear as appropriate:

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally

required.

No personal respiratory protective equipment normally

Valvoline,

SAFETY DATA SHEET

Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Melting point/freezing point : < -39 °C

Boiling point/boiling range : No data available

Flash point : 180 °C

Method: Pensky-Martens closed cup

Evaporation rate : Not applicable

Flammability (solid, gas) : No data available

Upper explosion limit / Upper :

flammability limit

No data available

Lower explosion limit / Lower :

flammability limit

No data available

Vapour pressure : No data available

Relative vapour density : No data available

Relative density : No data available

Density : ca. 0,872 g/cm3 (15 $^{\circ}$ C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : insoluble



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Not applicable

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : ca. 49,2 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11: Toxicological information

Valvoline...

Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

OLEFINSULFIDE:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

Components:

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and s:

Acute oral toxicity : LD50 (Rat): ca. 2.000 mg/kg

Method: OECD Test Guideline 401

Assessment: The component/mixture is classified as acute

oral toxicity, category 4.

Skin corrosion/irritation

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

HEAVY PARAFFINIC DISTILLATE:



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Result: Slight, transient irritation

OLEFINSULFIDE:

Result: Mild skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

OLEFINSULFIDE:

Result: Slight, transient irritation

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and s:

Result: Corrosive

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Components:

OLEFINSULFIDE:

Test Type: Maximisation Test

Species: Guinea pig

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 406

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and s:

Assessment: The product is a skin sensitiser, sub-category 1B.



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Germ cell mutagenicity

Not classified based on available information.

Components:

OLEFINSULFIDE:

Genotoxicity in vitro : Test Type: in vitro assay

Result: Positive results were obtained in some in vitro tests.

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse Cell type: Bone marrow

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Revision Date: 07.04.2020 Print Date: 14/09/2022 Version: 6.0

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

: This product has no known ecotoxicological effects.

Long-term (chronic) aquatic

hazard

: This product has no known ecotoxicological effects.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Aquatic invertebrates): > 10.000 mg/l

Exposure time: 48 h

: EL50 (Algae, algal mat (Algae)): > 100 mg/l Toxicity to algae

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC 10 mg/l Species: Fish

Toxicity to daphnia and other : NOEC: 10 mg/l

aquatic invertebrates

(Chronic toxicity)

Species: Aquatic invertebrates

Di-tert-butyl polysulfide **Ecotoxicology Assessment**

Short-term (acute) aquatic

hazard

Harmful to aquatic life.

Long-term (chronic) aquatic : Harmful to aquatic life with long lasting effects.

hazard

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): ca. 24 mg/l

> Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Revision Date: 07.04.2020 Print Date: 14/09/2022 Version: 6.0

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): ca. 91,4 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 15

ma/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 3,3

mg/l

End point: Growth inhibition Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other : NOEC: 0,12 mg/l

aquatic invertebrates

(Chronic toxicity)

Exposure time: 21 d

End point: Reproduction Test

Species: Daphnia magna (Water flea)

Test Type: semi-static test Test substance: WAF

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Short-term (acute) aquatic

hazard

Toxic to aquatic life.

Long-term (chronic) aquatic

hazard

: Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Components:

Di-tert-butyl polysulfide

Biodegradability : Result: Not readily biodegradable.

> Biodegradation: 13 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 7,4 % Exposure time: 28 d

Method: Modified Sturm Test

12.3 Bioaccumulative potential

Components:

Reaction products of 4-methyl-2-pentanol and diphosphorus pentasulfide, propoxylated, esterified with diphosphorus pentaoxide, and salted by amines, C12-14-tert-alkyl

Partition coefficient: n- : Remarks: No data available

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher...

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

: Not applicable

Regulation (EC) No 850/2004 on persistent organic

pollutants

: Not applicable

REACH - List of substances subject to authorisation

(Annex XIV)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

Not applicable



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

Quantity 1

Quantity 2

9b

Dangerous for the environment

200 t

500 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI: On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Simplified notification-Special case, 2% polymer

TCSI : On the inventory, or in compliance with the inventory

TSCA : On TSCA Inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information: R0517042



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Revision Date: 07.04.2020 Version: 6.0 Print Date: 14/09/2022

Full text of H-Statements

Harmful if swallowed. H302

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. Causes serious eye damage. H318

Toxic to aquatic life with long lasting effects. H411 Harmful to aquatic life with long lasting effects. H412

Other information : The information accumulated herein is believed to be accurate

but is not warranted to be whether originating with the

company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by

Valvoline's Environmental Health and Safety Department

('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI: Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population.



Valvoline™ GEAR OIL 75W80 RPC Gear Oil

Version: 6.0 Revision Date: 07.04.2020 Print Date: 14/09/2022

ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit P-Statement : Precautionary Statement PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase: Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class