Valvoline	Page: 1
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : SynPower™ FE SAE 5W30

Synthetic Motor Oil

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety dat	a
sheet	

Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39

3316 BG Dordrecht

Netherlands

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

Additional Labelling:

EUH210 Safety data sheet available on request.

EUH208 Contains C14-16-18 Alkyl phenol. May produce an allergic reaction.

2.3 Other hazards

Additional advice

No information available.

Valvoline	Page: 2
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC)	Concentration (%)
	Registration number	No 1272/2008)	` ,
Lubricating Oils	72623-87-1	Asp. Tox.1; H304	>= 80,00 - <
(Petroleum), C20-50,	276-738-4		90,00
Hydrotreated Neutral	01-2119474889-13-xxxx		
Oil-Based			
Reaction products of	36878-20-3	Aquatic Chronic4;	>= 1,00 - <
Benzeneamine, N-	01-2119488911-28-xxxx	H413	2,50
phenyl- with nonene			
(branched)			
Zinc bis[O-(6-	93819-94-4	Skin Irrit.2; H315	>= 1,00 - <
methylheptyl)] bis[O-	298-577-9	Eye Dam.1; H318	2,50
(sec-butyl)]	01-2119543726-33-xxxx	Aquatic Chronic2;	
bis(dithiophosphate)		H411	
C14-16-18 Alkyl phenol	931-468-2	Skin Sens.1B; H317	>= 1,00 - <
	01-2119498288-19-xxxx	STOT RE2; H373	2,50

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

Valvoline	Page: 3
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Signs and symptoms of exposure to this material through

breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Risks : Acute aspiration of large amounts of oil-laden material may

produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

nitrogen oxides (NOx)

zinc oxide Sulphur oxides hydrogen sulfide

Valvoline	Page: 4
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

mercaptans

5.3 Advice for firefighters

for firefighters

Special protective equipment : In the event of fire, wear self-contained breathing apparatus.

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Smoking, eating and drinking should be prohibited in the

application area.

For personal protection see section 8.

Advice on protection against

fire and explosion

: Normal measures for preventive fire protection.

: General industrial hygiene practice. Hygiene measures

Valvoline	Page: 5
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

7.2 Conditions for safe storage, including any incompatibilities

Advice on common storage : No materials to be especially mentioned.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

8.2 Exposure controls

Engineering measures

General room ventilation should be adequate for normal conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Respiratory protection : No personal respiratory protective equipment normally

required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

Valvoline	Page: 6
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

pH :

Not applicable

Pour point : < -39,00 °C

Boiling point/boiling range : > 225,00 °C

Flash point : 209 °C

Evaporation rate : Not applicable

Flammability (solid, gas) : No data available

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapour pressure : 25 hPa

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : ca. 0,852

Density : ca. 0,852 g/cm3 (15 °C)

Bulk density : Not applicable

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

Not applicable

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 9,8 mm2/s (100 °C)

ca. 54 mm2/s (40 °C)

Oxidizing properties : No data available

9.2 Other information

No data available

Valvoline.	Page: 7
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong bases

Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition

products

: carbon dioxide and carbon monoxide

hydrogen sulfide

Nitrogen oxides (NOx) Sulphur oxides zinc oxide fumes mercaptans

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of : Inhalation

exposure

Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5,58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Valvoline	Page: 8
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Remarks: No mortality observed at this dose.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: Information given is based on data obtained from

similar substances.

Components:

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Acute oral toxicity : LD50 (Rat): 2.600 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 3.160 mg/kg

Method: OECD Test Guideline 402

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Components:

C14-16-18 Alkyl phenol

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by ingestion under

GHS.

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Assessment: Not classified as acutely toxic by dermal

absorption under GHS.

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Species: Rabbit

Result: No skin irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Rabbit

Result: Mild skin irritation

Remarks: Information given is based on data obtained from similar substances.

Valvoline	
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Species: Guinea pig

Method: OECD Test Guideline 404

Result: Irritating to skin.

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Method: OECD Test Guideline 431

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Species: Rabbit

Result: No eye irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Species: Rabbit Result: Corrosive

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Species: Rabbit

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information. Respiratory sensitisation: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitisation.

Remarks: Based on similar product.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Valvoline.	Page: 10
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.

C14-16-18 Alkyl phenol

Test Type: Local lymph node assay

Species: Mouse

Assessment: The product is a skin sensitiser, sub-category 1B.

Method: OECD Test Guideline 429

Germ cell mutagenicity

Not classified based on available information.

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

Genotoxicity in vivo : Test Type: Micronucleus test

Test species: Mouse

Method: OECD Test Guideline 474

Result: negative

Remarks: Information given is based on data obtained from

similar substances.

C14-16-18 Alkyl phenol

Genotoxicity in vitro : Test Type: Ames test

Test species: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol

Valvoline	Page: 11
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Target Organs: Liver

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated

exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOELR: Calculated >= 1.000 mg/l

Exposure time: 14 d

Species: Oncorhynchus mykiss (rainbow trout)

Toxicity to daphnia and other

aquatic invertebrates

: NOEL: 10 mg/l Exposure time: 21 d

Valvoline	Page: 12
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

(Chronic toxicity) Species: Daphnia (water flea)

Test substance: WAF

Method: OECD Test Guideline 211

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Remarks: Information given is based on data obtained from

similar substances.

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l

> Exposure time: 96 h Test Type: semi-static test

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Water flea (Daphnia magna)): 5,4 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 2,1 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

C14-16-18 Alkyl phenol

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 100 mg/l

> Exposure time: 96 h Test Type: static test Test substance: WAF

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): > 100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test

Valvoline	Page: 13
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Test substance: WAF

12.2 Persistence and degradability

Components:

Lubricating Oils (Petroleum), C20-50, Hydrotreated Neutral Oil-Based Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
Biodegradability : Result: Not readily biodegradable.

Biodegradation: 1,5 % Exposure time: 28 d

Method: OECD Test Guideline 301B

C14-16-18 Alkyl phenol

Biodegradability : Result: Readily biodegradable.

Remarks: Expert judgement

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched)

Partition coefficient: n- : log Pow: > 7,5

octanol/water

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)
Partition coefficient: n- : log Pow: 0,59 - 1,2 (23 °C)

octanol/water

C14-16-18 Alkyl phenol

Partition coefficient: n- : log Pow: > 7,2

octanol/water

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Not relevant

Valvoline	Page: 14
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

12.6 Other adverse effects

Product:

Additional ecological

information

: No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Contaminated packaging : Empty remaining contents.

SECTION 14: Transport information

SECTION 14: Transport information

14.1 UN number

ADN: Not dangerous goods **ADR:** Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods

RID: Not dangerous goods

14.2 UN proper shipping name

ADN: Not dangerous goods **ADR:** Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods

RID: Not dangerous goods

14.3 Transport hazard class(es)

ADN: Not dangerous goods **ADR:** Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods

RID: Not dangerous goods

14.4 Packing group

ADN: Not dangerous goods **ADR:** Not dangerous goods

Valvoline	Page: 15
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not dangerous goods INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS: Not dangerous goods

RID: Not dangerous goods

14.5 Environmental hazards

ADN: Not applicable **ADR:** Not applicable

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO: Not applicable INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER: Not applicable

INTERNATIONAL MARITIME DANGEROUS GOODS: Not applicable

RID: Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Ship Type: Not applicable Hazard code(s): Not applicable Pollutant Category: Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 850/2004 on persistent organic : Not applicable

pollutants

REACH - List of substances subject to authorisation : Not applicable

(Annex XIV)

REACH - Restrictions on the manufacture, placing on

the market and use of certain dangerous substances,

preparations and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

: Not applicable

: Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

: Not applicable

Valvoline	
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL All components of this product are on the Canadian DSL

AICS On the inventory, or in compliance with the inventory

ENCS Not in compliance with the inventory

KECI On the inventory, or in compliance with the inventory

PICCS On the inventory, or in compliance with the inventory

IECSC On the inventory, or in compliance with the inventory

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 11.01.2017

Full text of H-Statements

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Valvoline	Page: 17
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

Other information

: The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE : Personal Protective Equipment STEL : Short-term exposure limit STOT : Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

Valvoline	Page: 18
SAFETY DATA SHEET	Revision Date: 11.01.2017
	Print Date: 16.09.2022
	SDS Number: 000000098054
SynPower™ FE SAE 5W30 Synthetic Motor Oil	Version: 2.2
872551	

ABM: Water Hazard Class for the Netherlands

ADR: Agreement concerning the International Carriage of Dangerous Goods by Road.

ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine

CLP: Classification, Labelling and Packaging

CSA: Chemical Safety Assessment CSR: Chemical Safety Report DNEL: Derived No Effect Level.

EINECS: European Inventory of Existing Commercial Chemical Substances.

ELINCS: European List of Notified Chemical Substances

PEC : Predicted Effect Concentration PEL : Permissible Exposure Limits

PNEC: Predicted No Effect Concentration

R-phrase : Risk phrase

REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail

S-phrase: Safety phrase

WGK: German Water Hazard Class