



SAFETY DATA SHEET

This safety data sheet complies with the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

Revision Date 25-Jul-2016

Version 2

Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Code 80331
Product Name MB-1 MUFFLER & TAILPIPE BANDAGE KT CG

Contains BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Automotive Care Product

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Importer

ITW Permatex
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839

E-mail address

mail@permatex.com

1.4. Emergency telephone number

24 Hour Emergency Phone Number - 800-255-3924 (00+ 1+ 813-248-0585) ChemTel

Section 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Skin corrosion/irritation	Category 2 - (H315)
Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitization	Category 1 - (H317)
Chronic aquatic toxicity	Category 2 - (H411)

Classification according to Directive 67/548/EEC or 1999/45/EC

Full text of R-phrases: see section 16

2.2. Label elements

Contains BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN



Signal word
Warning

Statements of hazard

H315 - Causes skin irritation

H317 - May cause an allergic skin reaction

H319 - Causes serious eye irritation

H411 - Toxic to aquatic life with long lasting effects

Precautionary Statements - EU (§28, 1272/2008)

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P280 - Wear eye protection/ face protection

P273 - Avoid release to the environment

P321 - Specific treatment (see supplemental first aid instructions on this label)

Other Information

- Not applicable

Section 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.1 substances**

Chemical Name	EC No	CAS No	Weight-%	Classification according to Directive 67/548/EEC or 1999/45/EC	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH Registration Number
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	-	25068-38-6	30-40	Xi; R36/38 R43 N; R51-53	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	No data available
METHYL ETHYL KETONE (BUTANONE)	201-159-0	78-93-3	<3	F; R11 Xi; R36 R66 R67	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	No data available

Full text of R-phrases: see section 16

Full text of H- and EUH-phrases: see section 16

Section 4: FIRST AID MEASURES**4.1. Description of first aid measures****General advice**

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.

Skin contact

IF ON SKIN: Wash with soap and water. If skin irritation or rash occurs: Get medical

advice/attention. Wash contaminated clothing before reuse.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion IF SWALLOWED: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information

4.3. Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂). Foam. Dry chemical.

Unsuitable extinguishing media

No information available

5.2. Special hazards arising from the substance or mixture

None in particular.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit. Use personal protective equipment as required.

Section 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Wash thoroughly after handling.

For emergency responders

Use personal protection recommended in Section 8.

6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

6.3. Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Ensure adequate ventilation. Sweep up and shovel into suitable containers for disposal.

6.4. Reference to other sections

See section 8 for more information. See section 13 for more information.

Section 7: HANDLING AND STORAGE

7.1. Precautions for safe handling**Advice on safe handling**

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Avoid breathing vapors or mists.

General Hygiene Considerations

Do not eat, drink or smoke when using this product. Take off all contaminated clothing and wash it before reuse. Wash hands thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep container tightly closed in a dry and well-ventilated place.

Incompatible materials

Strong oxidizing agents, Reducing agents

7.3. Specific end use(s)**Specific use(s)**

Automotive Care Product.

Risk Management Methods (RMM)

The information required is contained in this Safety Data Sheet.

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Chemical Name	European Union	United Kingdom	France	Spain	Germany
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA 200 ppm TWA 600 mg/m ³ STEL 300 ppm STEL 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 899 mg/m ³ Sk*	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ *	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ H*
Chemical Name	Italy	Portugal	Netherlands	Finland	Denmark
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³	TWA: 590 mg/m ³ STEL: 900 mg/m ³ H*	STEL: 100 ppm STEL: 300 mg/m ³ iho*	TWA: 50 ppm TWA: 145 mg/m ³ H*
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
METHYL ETHYL KETONE (BUTANONE) 78-93-3	TWA: 100 ppm TWA: 295 mg/m ³ STEL 200 ppm STEL 590 mg/m ³ H*	TWA: 200 ppm TWA: 590 mg/m ³ STEL: 200 ppm STEL: 590 mg/m ³ H*	STEL: 900 mg/m ³ TWA: 450 mg/m ³	TWA: 75 ppm TWA: 220 mg/m ³ STEL: 75 ppm STEL: 220 mg/m ³	TWA: 200 ppm TWA: 600 mg/m ³ STEL: 300 ppm STEL: 900 mg/m ³ Sk*

Chemical Name	European Union	United Kingdom	France	Spain	Germany
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	70	-	2	2 mg/L
Chemical Name	Austria	Switzerland	Poland	Norway	Ireland
METHYL ETHYL KETONE (BUTANONE) 78-93-3	-	2	-	-	-

Derived No Effect Level (DNEL) No information available.

Predicted No Effect Concentration (PNEC) No information available.

8.2. Exposure controls

Engineering Controls	Use exhaust ventilation to keep airborne concentrations below exposure limits.
Personal protective equipment	
Eyeface protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Suitable protective clothing. Gloves made of plastic or rubber.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment. Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
Environmental exposure controls	Local authorities should be advised if significant spillages cannot be contained.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state	Solid
Appearance	White
Odor	Ketone
Odor threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	No information available	
Flash point	No information available	
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density		
Water solubility	No information available	
Solubility(ies)	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

9.2. Other information

Softening point	No information available
Molecular weight	No information available
VOC Content (%)	1.5%
Density	No information available
Bulk density	No information available

Section 10: STABILITY AND REACTIVITY

10.1. Reactivity

Not applicable

10.2. Chemical stability

Stable under normal conditions.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

10.3. Possibility of hazardous reactions

None under normal processing.

10.4. Conditions to avoid

Excessive heat.

10.5. Incompatible materials

Strong oxidizing agents

Reducing agents

10.6. Hazardous decomposition products

Carbon oxides

Ketones and their derivatives

Hydrogen fluoride

Section 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects****Product Information****Inhalation**

May cause irritation of respiratory tract.

Eye contact

Irritating to eyes. May cause redness and tearing of the eyes.

Skin contact

May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.

Ingestion

Ingestion may cause irritation to mucous membranes.

The following values are calculated based on chapter 3.1 of the GHS document**ATEmix (oral)** 9,968.00 mg/kg**ATEmix (dermal)** 5,000.00 mg/kg**ATEmix (inhalation-vapor)** 11,700.00 mg/l**Unknown acute toxicity**

100 % of the mixture consists of ingredient(s) of unknown toxicity.

62.5 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

98.5 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

98.5 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	= 11400 mg/kg (Rat)		
METHYL ETHYL KETONE (BUTANONE)	= 2483 mg/kg (Rat) = 2737 mg/kg (Rat)	= 5000 mg/kg (Rabbit) = 6480 mg/kg (Rabbit)	= 11700 ppm (Rat) 4 h

Skin corrosion/irritation No information available.**Serious eye damage/eye irritation** No information available.**Sensitization** No information available.

Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Target Organ Effects	Central nervous system, Eyes, Respiratory system, Skin.
Aspiration hazard:	No information available.

Section 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity Toxic to aquatic life with long lasting effects.

Chemical Name	Algae/aquatic plants	Fish	Crustacea
METHYL ETHYL KETONE (BUTANONE)	-	3130 - 3320: 96 h Pimephales promelas mg/L LC50 flow-through	4025 - 6440: 48 h Daphnia magna mg/L EC50 Static 5091: 48 h Daphnia magna mg/L EC50 520: 48 h Daphnia magna mg/L EC50

12.2. Persistence and degradability

No information available.

12.3. Bioaccumulative potential

No information available.

Chemical Name	Partition coefficient
METHYL ETHYL KETONE (BUTANONE)	0.3

12.4. Mobility in soil

Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

No information available.

12.6. Other adverse effects

No information available

Endocrine Disruptor Information

Chemical Name	EU - Endocrine Disruptors Candidate List	EU - Endocrine Disruptors - Evaluated Substances	Endocrine disrupting potential
BISPHENOL A/EPICHLOROHYDRIN BASED EPOXY RESIN	Group III Chemical	-	-

Section 13: DISPOSAL CONSIDERATIONS**13.1. Waste treatment methods**

Waste from residues/unused products	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
Waste codes / waste designations according to EWC / AVV	No data available
Other Information	Waste codes should be assigned by the user based on the application for which the product was used.

Section 14: TRANSPORT INFORMATION**IMDG**

14.1 UN/ID no	Not regulated
14.2 Proper shipping name:	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 EmS-No	Not applicable

RID

14.1 UN/ID no	Not regulated
14.2 Proper shipping name:	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	No information available

ADR

14.1 UN/ID no	Not regulated
14.2 Proper shipping name:	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 Classification code	No information available

IATA

14.1 UN/ID no	Not regulated
14.2 Proper shipping name:	Not regulated
14.3 Hazard Class	Not regulated
14.4 Packing Group	None
14.5 Environmental hazard	Not applicable
14.6 Special Provisions	No information available
14.7 ERG Code	Not applicable

Section 15: REGULATORY INFORMATION**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Chemical Name	French RG number	Title
---------------	------------------	-------

METHYL ETHYL KETONE (BUTANONE) 78-93-3	RG 84	-
---	-------	---

European Union

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Authorizations and/or restrictions on use:

This product does not contain substances subject to authorization (Regulation (EC) No. 1907/2006 (REACH), Annex XIV) This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII)

Persistent Organic Pollutants

Not applicable

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

International Inventories

TSCA	Complies
DSL/NDL	Complies
EINECS/ELINCS	Complies
ENCS	Complies
IECSC	Complies
KECL	Complies
PICCS	Complies
AICS	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

15.2. Chemical safety assessment

No information available

Section 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of R-phrases referred to under sections 2 and 3

No information available

Full text of H-Statements referred to under section 3

H315 - Causes skin irritation
H319 - Causes serious eye irritation
H317 - May cause an allergic skin reaction
H411 - Toxic to aquatic life with long lasting effects
H336 - May cause drowsiness or dizziness
H225 - Highly flammable liquid and vapor
EUH066 - Repeated exposure may cause skin dryness or cracking

Legend

SVHC: Substances of Very High Concern for Authorization:

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Revision Date 25-Jul-2016

Revision Note Not applicable.

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

End of Safety Data Sheet