



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 13

TEROSON VR 100 NANO

SDS No. : 415502
V004.0

Revision: 28.02.2023

printing date: 25.07.2023

Replaces version from: 12.06.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON VR 100 NANO

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Cleaners for Automobile

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Ethanol denatured 64-17-5 200-578-6 01-2119457610-43	5- < 10 %	Flam. Liq. 2, H225 Eye Irrit. 2, H319	Eye Irrit. 2; H319; C > 50 %	
1-Butoxypropan-2-ol 5131-66-8 225-878-4 01-2119475527-28	1- < 5 %	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Flam. Liq. 3, H226		

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

Declaration of ingredients according to Detergent Regulation 648/2004/EC

II contains **Perfumes**

Allergenic fragrance ingredients ≥ 100 ppm: Limonene

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Immediately wash skin thoroughly with soap and water.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media**Suitable extinguishing media:**

Carbon dioxide, foam, powder
Water spray jet

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in fires.

5.3. Advice for firefighters

Wear protective equipment.

Additional information:

Cool endangered containers with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove with liquid-absorbing material (sand, peat, sawdust).
Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Avoid skin and eye contact.
Ensure that workrooms are adequately ventilated.
See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.
Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container.
The alterations have no negative influence on the product quality and stability.
Alterations are reversible after warming to room temperature.
Must be stored in a room with spill collection facilities.
Store in a cool place.
Keep container tightly sealed.
Keep container in a well ventilated place.
Do not use packing made of metal.
Store in a cool, well-ventilated place.
Keep away from food, beverages and animal feed.
Do not store together with strong bases or very alkaline substances.

7.3. Specific end use(s)

Cleaners for Automobile

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000	1.920	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Ethanol 64-17-5 [ETHANOL]	1.000		Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Ethanol denatured 64-17-5	aqua (freshwater)		0,96 mg/l				
Ethanol denatured 64-17-5	aqua (marine water)		0,79 mg/l				
Ethanol denatured 64-17-5	sediment (freshwater)				3,6 mg/kg		
Ethanol denatured 64-17-5	Soil				0,63 mg/kg		
Ethanol denatured 64-17-5	sediment (marine water)				2,9 mg/kg		
Ethanol denatured 64-17-5	oral				0,72 mg/kg		
Ethanol denatured 64-17-5	sewage treatment plant (STP)		580 mg/l				
Ethanol denatured 64-17-5	aqua (intermittent releases)		2,75 mg/l				
1-Butoxypropan-2-ol 5131-66-8	aqua (freshwater)		0,525 mg/l				
1-Butoxypropan-2-ol 5131-66-8	aqua (marine water)		0,0525 mg/l				
1-Butoxypropan-2-ol 5131-66-8	aqua (intermittent releases)		5,25 mg/l				
1-Butoxypropan-2-ol 5131-66-8	sewage treatment plant (STP)		10 mg/l				
1-Butoxypropan-2-ol 5131-66-8	sediment (freshwater)				2,36 mg/kg		
1-Butoxypropan-2-ol 5131-66-8	sediment (marine water)				0,236 mg/kg		
1-Butoxypropan-2-ol 5131-66-8	Soil				0,16 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Ethanol denatured 64-17-5	Workers	Inhalation	Acute/short term exposure - local effects		1900 mg/m3	
Ethanol denatured 64-17-5	Workers	dermal	Long term exposure - systemic effects		343 mg/kg	
Ethanol denatured 64-17-5	Workers	Inhalation	Long term exposure - systemic effects		950 mg/m3	
Ethanol denatured 64-17-5	General population	Inhalation	Acute/short term exposure - local effects		950 mg/m3	
Ethanol denatured 64-17-5	General population	dermal	Long term exposure - systemic effects		206 mg/kg	
Ethanol denatured 64-17-5	General population	Inhalation	Long term exposure - systemic effects		114 mg/m3	
Ethanol denatured 64-17-5	General population	oral	Long term exposure - systemic effects		87 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Long term exposure - systemic effects		52 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	inhalation	Long term exposure - systemic effects		147 mg/m3	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Long term exposure - systemic effects		22 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	General population	inhalation	Long term exposure - systemic effects		43 mg/m3	
1-Butoxypropan-2-ol 5131-66-8	General population	oral	Long term exposure - systemic effects		12,5 mg/kg	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Acute/short term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	Workers	dermal	Long term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Acute/short term exposure - local effects		50 %	
1-Butoxypropan-2-ol 5131-66-8	General population	dermal	Long term exposure - local effects		50 %	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/suction at the workplace.

Respiratory protection:

In case of aerosol formation, we recommend wearing of appropriate respiratory protection equipment with ABEK P2 filter (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; ≥ 1 mm thickness) or natural rubber (NR; ≥ 1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; ≥ 1 mm thickness) or natural rubber (NR; ≥ 1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Suitable protective clothing

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state	liquid
Delivery form	liquid
Colour	blue
Odor	Alcohol-like
Melting point	Not applicable, Product is a liquid
Solidification temperature	$< -5\text{ }^{\circ}\text{C}$ ($< 23\text{ }^{\circ}\text{F}$)
Initial boiling point	$95\text{ }^{\circ}\text{C}$ ($203\text{ }^{\circ}\text{F}$)
Flammability	Currently under determination
Explosive limits	Currently under determination
Flash point	$51\text{ }^{\circ}\text{C}$ ($123.8\text{ }^{\circ}\text{F}$); flash point, Abel-Pensky
	The product does not support combustion in any way.
Auto-ignition temperature	Currently under determination
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	10,0 - 10,6 PH-value, potentiometer
($20\text{ }^{\circ}\text{C}$ ($68\text{ }^{\circ}\text{F}$); Conc.: 100 % product)	
Viscosity (kinematic)	Currently under determination
Solubility (qualitative)	Miscible
($20\text{ }^{\circ}\text{C}$ ($68\text{ }^{\circ}\text{F}$); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	Currently under determination
Density	$0,988 - 0,998\text{ g/cm}^3$ density, weight
($20\text{ }^{\circ}\text{C}$ ($68\text{ }^{\circ}\text{F}$))	
Relative vapour density:	Currently under determination
Particle characteristics	Not applicable
	Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reaction with strong oxidants.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

No decomposition if used according to specifications.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

None if used for intended purpose.

In case of fire toxic gases can be released.

SECTION 11: Toxicological information

General toxicological information:

To the best of our knowledge no harmful effects are to be expected if the product is handled and used properly.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	10.470 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
1-Butoxypropan-2-ol 5131-66-8	LD50	3.300 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Ethanol denatured 64-17-5	LD50	> 2.000 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
1-Butoxypropan-2-ol 5131-66-8	LD50	3.133 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Ethanol denatured 64-17-5	LC50	124,7 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
1-Butoxypropan-2-ol 5131-66-8	LC50	> 651 ppm	vapour	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
1-Butoxypropan-2-ol 5131-66-8	moderately irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Ethanol denatured 64-17-5	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Ethanol denatured 64-17-5	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
1-Butoxypropan-2-ol 5131-66-8	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
1-Butoxypropan-2-ol 5131-66-8	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
1-Butoxypropan-2-ol 5131-66-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1-Butoxypropan-2-ol 5131-66-8	negative	in vitro mammalian chromosome aberration test	with and without		equivalent or similar to OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1-Butoxypropan-2-ol 5131-66-8	negative	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
1-Butoxypropan-2-ol 5131-66-8	NOAEL P 300 ppm NOAEL F1 1000 ppm NOAEL F2 1000 ppm	Two generation study	inhalation: vapour	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
1-Butoxypropan-2-ol 5131-66-8	NOAEL 350 mg/kg	oral: drinking water	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
1-Butoxypropan-2-ol 5131-66-8	NOAEL 600 ppm	inhalation	11 d 6h/d	rat	equivalent or similar to OECD Guideline 412 (Repeated Dose Inhalation Toxicity: 28/14-Day)
1-Butoxypropan-2-ol 5131-66-8	NOAEL 880 mg/kg		13 w 5 d/w	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

The biodegradability of the surfactants contained in the product is in accordance with the requirements of the EU Detergent Regulation (EC/648/2004).

The surfactants contained in the products are primary biodegradable to at least 90% on average.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	LC50	> 12.000 - 16.000 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
1-Butoxypropan-2-ol 5131-66-8	LC50	1.732 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	not specified

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
1-Butoxypropan-2-ol 5131-66-8	EC50	> 700 mg/l	24 h	Daphnia magna	not specified

Chronic toxicity to aquatic invertebrates

No data available.

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	EC50	> 100 mg/l	24 h	Chlorella pyrenoidosa	OECD Guideline 201 (Alga, Growth Inhibition Test)
1-Butoxypropan-2-ol 5131-66-8	EC50	1.466 mg/l		Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Ethanol denatured 64-17-5	IC50	> 1.000 mg/l	3 h	activated sludge	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
1-Butoxypropan-2-ol 5131-66-8	EC0	10.000 mg/l	30 min		not specified

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Ethanol denatured 64-17-5	readily biodegradable	aerobic	> 70 %	5 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
1-Butoxypropan-2-ol 5131-66-8	readily biodegradable	aerobic	80 - 90 %	30 d	EU Method C.4-E (Determination of the "Ready" Biodegradability Closed Bottle Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Ethanol denatured 64-17-5	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
1-Butoxypropan-2-ol 5131-66-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

If acidic or alkaline products are discharged into wastewater installations care must be taken that the discharged wastewater has a pH in the range pH 6 - 10, as pH variations could cause disorders in wastewater channels and biological sewage treatment plants. The local discharge regulations take precedence.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

EWC/EAK 070608

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information

- 14.1. UN number or ID number**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.2. UN proper shipping name**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.3. Transport hazard class(es)**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.4. Packing group**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.5. Environmental hazards**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.6. Special precautions for user**
Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.
- 14.7. Maritime transport in bulk according to IMO instruments**
not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EU)	8,5 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

National regulations/information (Great Britain):

Remarks	Control of Substances Hazardous to Health Regulations (COSHH), and related guidance, e.g COSHH Essentials. EH40 Occupational Exposure Limits Chemicals (Hazard Information & Packaging for Supply) Regulations. The Personnel Protective Equipment at Work Regulations. The Carriage of Dangerous Goods by Road Regulations. The Health & Safety at Work Act 1974. (Note: Use latest editions/amendments of above referenced documents.)
---------	--

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.