

Page 1 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.03.2018 / 0014
Replacing version dated / version: 27.09.2016 / 0013
Valid from: 23.03.2018
PDF print date: 28.03.2018
Profi Leichtlauf 10W-40 Basic 60 L
Art.: 7762

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Profi Leichtlauf 10W-40 Basic 60 L
Art.: 7762

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Motor oil

Sector of use [SU]:

SU 3 - Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 - Consumer uses: Private households (=general public = consumers)

SU22 - Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Chemical product category [PC]:

PC17 - Hydraulic fluids

PC24 - Lubricants, greases, release products

Process category [PROC]:

PROC 1 - Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions.

PROC 2 - Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

PROC 8a - Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC 8b - Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC 9 - Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC20 - Use of functional fluids in small devices

Article Categories [AC]:

AC99 - Not required.

Environmental Release Category [ERC]:

ERC 4 - Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

ERC 7 - Use of functional fluid at industrial site

ERC 9a - Widespread use of functional fluid (indoor)

ERC 9b - Widespread use of functional fluid (outdoor)

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

LIQUI MOLY GmbH, Jerg-Wieland-Str. 4, 89081 Ulm-Lehr, Germany
Phone:(+49) 0731-1420-0, Fax:(+49) 0731-1420-88

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (LMR)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.03.2018 / 0014
Replacing version dated / version: 27.09.2016 / 0013
Valid from: 23.03.2018
PDF print date: 28.03.2018
Profi Leichtlauf 10W-40 Basic 60 L
Art.: 7762

Classification according to Regulation (EC) 1272/2008 (CLP)

The mixture is not classified as dangerous in the terms of the Regulation (EC) 1272/2008 (CLP).

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

EUH210-Safety data sheet available on request.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

Hazardous to drinking water, on escape of even small quantities.

Product can compose a film on the water surface, which can prevent oxygen exchange.

SECTION 3: Composition/information on ingredients

3.1 Substance

n.a.

3.2 Mixture

Distillates (petroleum), hydrotreated light paraffinic	
Registration number (REACH)	01-2119487077-29-XXXX
Index	649-468-00-3
EINECS, ELINCS, NLP	265-158-7
CAS	64742-55-8
content %	0-26
Classification according to Regulation (EC) 1272/2008 (CLP)	Asp. Tox. 1, H304

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)	
Substance with specific conc. limit(s) acc. to REACH-registration	
Registration number (REACH)	01-2119543726-33-XXXX
Index	---
EINECS, ELINCS, NLP	298-577-9
CAS	93819-94-4
content %	0,1-2,5
Classification according to Regulation (EC) 1272/2008 (CLP)	Skin Irrit. 2, H315 Eye Dam. 1, H318 Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.

The substances named in this section are given with their actual, appropriate classification!

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

Skin contact

Page 3 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.03.2018 / 0014
Replacing version dated / version: 27.09.2016 / 0013
Valid from: 23.03.2018
PDF print date: 28.03.2018
Profi Leichtlauf 10W-40 Basic 60 L
Art.: 7762

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.

Call doctor immediately - have Data Sheet available.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

Irritation of the eyes

With long-term contact:

Drying of the skin.

Dermatitis (skin inflammation)

With oil mist formation:

Irritation of the respiratory tract

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

CO₂

Foam

Dry extinguisher

Large fire:

Water jet spray / alcohol resistant foam

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Oxides of nitrogen

Oxides of phosphorus

Toxic gases

Hot product gives off combustible vapours.

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid formation of oil mist.

Remove possible causes of ignition - do not smoke.

Avoid contact with eyes or skin.

If applicable, caution - risk of slipping.

6.2 Environmental precautions

If leakage occurs, dam up.

Resolve leaks if this possible without risk.

Prevent from entering drainage system.

Prevent surface and ground-water infiltration, as well as ground penetration.

If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

Page 4 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.03.2018 / 0014
 Replacing version dated / version: 27.09.2016 / 0013
 Valid from: 23.03.2018
 PDF print date: 28.03.2018
 Profi Leichtlauf 10W-40 Basic 60 L
 Art.: 7762

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
 Oil binder

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Avoid contact with eyes.
 Avoid formation of oil mist.
 Avoid long lasting or intensive contact with skin.
 Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
 Do not heat to temperatures close to flash point.
 Do not carry cleaning cloths soaked in product in trouser pockets.
 Observe directions on label and instructions for use.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Not to be stored in gangways or stair wells.
 Store product closed and only in original packing.
 Protect against moisture and store closed.
 Store at room temperature.

7.3 Specific end use(s)

No information available at present.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name	Oil mist, mineral	Content %:
WEL-TWA: 5 mg/m3 (ACGIH)	WEL-STEL: 10 mg/m3 (ACGIH)	---
Monitoring procedures:	- Draeger - Oil 10/a-P (67 28 371) - Draeger - Oil Mist 1/a (67 33 031)	
BMGV: ---	Other information: ---	

WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).
 (8) = Inhalable fraction (2017/164/EU). (9) = Respirable fraction (2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 ** = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.

8.2 Exposure controls

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,004	mg/l	
	Environment - marine		PNEC	0,0046	mg/l	

Page 5 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.03.2018 / 0014
 Replacing version dated / version: 27.09.2016 / 0013
 Valid from: 23.03.2018
 PDF print date: 28.03.2018
 Profi Leichtlauf 10W-40 Basic 60 L
 Art.: 7762

	Environment - sediment, freshwater		PNEC	0,0116	mg/kg	
	Environment - sediment, marine		PNEC	0,00116	mg/kg	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - soil		PNEC	0,00528	mg/kg	
	Environment - oral (animal feed)		PNEC	10,67	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,11	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	0,29	mg/kg	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,24	mg/kg	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	8,31	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	0,58	mg/kg	

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
 Applies only if maximum permissible exposure values are listed here.
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
 These are specified by e.g. BS EN 14042.
 BS EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
 Wash hands before breaks and at end of work.
 Keep away from food, drink and animal feedingstuffs.
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
 Protective gloves, oil resistant (EN 374)
 If applicable
 Protective nitrile gloves (EN 374)
 Protective Neoprene® / polychloroprene gloves (EN 374).
 Protective PVC gloves (EN 374)
 Minimum layer thickness in mm:
 0,35
 Permeation time (penetration time) in minutes:
 >= 480
 Protective hand cream recommended.
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
 Normally not necessary.
 With oil mist formation:
 Filter A2 P2 (EN 14387), code colour brown, white
 Observe wearing time limitations for respiratory protection equipment.

Page 6 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.03.2018 / 0014
 Replacing version dated / version: 27.09.2016 / 0013
 Valid from: 23.03.2018
 PDF print date: 28.03.2018
 Profi Leichtlauf 10W-40 Basic 60 L
 Art.: 7762

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Brown
Odour:	Characteristic
Odour threshold:	Not determined
pH-value:	Not determined
Melting point/freezing point:	Not determined
Initial boiling point and boiling range:	Not determined
Flash point:	222 °C
Evaporation rate:	Not determined
Flammability (solid, gas):	n.a.
Lower explosive limit:	Not determined
Upper explosive limit:	Not determined
Vapour pressure:	Not determined
Vapour density (air = 1):	Not determined
Density:	0,870 g/ml
Bulk density:	n.a.
Solubility(ies):	Not determined
Water solubility:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
Auto-ignition temperature:	Not determined
Decomposition temperature:	Not determined
Viscosity:	94,7 mm ² /s (40°C)
Viscosity:	13,9 mm ² /s (100°C)
Explosive properties:	Product is not explosive.
Oxidising properties:	No

9.2 Other information

Miscibility:	Not determined
Fat solubility / solvent:	Not determined
Conductivity:	Not determined
Surface tension:	Not determined
Solvents content:	Not determined

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

See also section 7.

Page 7 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.03.2018 / 0014
 Replacing version dated / version: 27.09.2016 / 0013
 Valid from: 23.03.2018
 PDF print date: 28.03.2018
 Profi Leichtlauf 10W-40 Basic 60 L
 Art.: 7762

Protect from humidity.
 Open flame, ignition sources

10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Possibly more information on health effects, see Section 2.1 (classification).

Profi Leichtlauf 10W-40 Basic 60 L

Art.: 7762

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Distillates (petroleum), hydrotreated light paraffinic

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat		
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rat	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>5	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Aerosol
Specific target organ toxicity - repeated exposure (STOT-RE):	LOAEL	125	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Aspiration hazard:						Yes

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	2600	mg/kg	Rat		
Acute toxicity, by dermal route:	LD50	>3160	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>2	mg/l/1h	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Skin corrosion/irritation:		>=6,25	%	Guinea pig	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Sens. 1, Analogous conclusion
Serious eye damage/irritation:		504	h	Rabbit		Eye Dam. 1, Analogous conclusion16 CFR 1500.42

Page 8 of 12
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 23.03.2018 / 0014
 Replacing version dated / version: 27.09.2016 / 0013
 Valid from: 23.03.2018
 PDF print date: 28.03.2018
 Profi Leichtlauf 10W-40 Basic 60 L
 Art.: 7762

Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative, Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):	NOAEL	160	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	Analogous conclusion, Negative

SECTION 12: Ecological information

Possibly more information on environmental effects, see Section 2.1 (classification).

Profi Leichtlauf 10W-40 Basic 60 L Art.: 7762

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							Not totally biodegradable.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Other adverse effects:							n.d.a.

Distillates (petroleum), hydrotreated light paraffinic

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50		>100	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	>10000	mg/l		OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	4,5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EL50	48h	5,4	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	EbC50	96h	2,1	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	1,5	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Not readily biodegradable

Page 9 of 12
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 23.03.2018 / 0014
Replacing version dated / version: 27.09.2016 / 0013
Valid from: 23.03.2018
PDF print date: 28.03.2018
Profi Leichtlauf 10W-40 Basic 60 L
Art.: 7762

12.3. Bioaccumulative potential:	Log Pow		0,59-1,2			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:			10	mg/l	activated sludge		

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

Soaked polluted cloths, paper or other organic materials represent a fire hazard and should be controlled, collected and disposed of.
EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product.
Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
13 02 05 mineral-based non-chlorinated engine, gear and lubricating oils

Recommendation:

Sewage disposal shall be discouraged.
Pay attention to local and national official regulations.
Implement substance recycling.
E.g. suitable incineration plant.
Observe regulations for disposal of old oil/waste.

For contaminated packing material

Pay attention to local and national official regulations.
Empty container completely.
Uncontaminated packaging can be recycled.
Dispose of packaging that cannot be cleaned in the same manner as the substance.
15 01 01 paper and cardboard packaging
15 01 02 plastic packaging
15 01 04 metallic packaging

SECTION 14: Transport information

General statements

14.1. UN number: n.a.

Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
Classification code: n.a.
LQ: n.a.
14.5. Environmental hazards: Not applicable
Tunnel restriction code:

Transport by sea (IMDG-code)

14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
Marine Pollutant: n.a.
14.5. Environmental hazards: Not applicable

Transport by air (IATA)

14.2. UN proper shipping name:
14.3. Transport hazard class(es): n.a.
14.4. Packing group: n.a.
14.5. Environmental hazards: Not applicable

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2018 / 0014

Replacing version dated / version: 27.09.2016 / 0013

Valid from: 23.03.2018

PDF print date: 28.03.2018

Profi Leichtlauf 10W-40 Basic 60 L

Art.: 7762

14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Non-dangerous material according to Transport Regulations.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

General hygiene measures for the handling of chemicals are applicable.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

4, 8, 15

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Not applicable

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.

Asp. Tox. — Aspiration hazard

Skin Irrit. — Skin irritation

Eye Dam. — Serious eye damage

Aquatic Chronic — Hazardous to the aquatic environment - chronic

Any abbreviations and acronyms used in this document:

AC Article Categories

acc., acc. to according, according to

ACGIH American Conference of Governmental Industrial Hygienists

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)

AOEL Acceptable Operator Exposure Level

AOX Adsorbable organic halogen compounds

approx. approximately

Art., Art. no. Article number

ATE Acute Toxicity Estimate according to Regulation (EC) 1272/2008 (CLP)

BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)

BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)

BCF Bioconcentration factor

BGV Berufsgenossenschaftliche Vorschrift (= Accident Prevention Regulation)

BHT Butylhydroxytoluol (= 2,6-Di-*t*-butyl-4-methyl-phenol)

BMGV Biological monitoring guidance value (EH40, UK)

BOD Biochemical oxygen demand

BSEF Bromine Science and Environmental Forum

bw body weight

CAS Chemical Abstracts Service

CEC	Coordinating European Council for the Development of Performance Tests for Fuels, Lubricants and Other Fluids
CESIO	Comité Européen des Agents de Surface et de leurs Intermédiaires Organiques
CIPAC	Collaborative International Pesticides Analytical Council
CLP	Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
CMR	carcinogenic, mutagenic, reproductive toxic
COD	Chemical oxygen demand
CTFA	Cosmetic, Toiletry, and Fragrance Association
DMEL	Derived Minimum Effect Level
DNEL	Derived No Effect Level
DOC	Dissolved organic carbon
DT50	Dwell Time - 50% reduction of start concentration
DVS	Deutscher Verband für Schweißen und verwandte Verfahren e.V. (= German Association for Welding and Allied Processes)
dw	dry weight
e.g.	for example (abbreviation of Latin 'exempli gratia'), for instance
EC	European Community
ECHA	European Chemicals Agency
EEA	European Economic Area
EEC	European Economic Community
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
EN	European Norms
EPA	United States Environmental Protection Agency (United States of America)
ERC	Environmental Release Categories
ES	Exposure scenario
etc.	et cetera
EU	European Union
EWC	European Waste Catalogue
Fax.	Fax number
gen.	general
GHS	Globally Harmonized System of Classification and Labelling of Chemicals
GWP	Global warming potential
HET-CAM	Hen's Egg Test - Chorionallantoic Membrane
HGWP	Halocarbon Global Warming Potential
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IBC	Intermediate Bulk Container
IBC (Code)	International Bulk Chemical (Code)
IC	Inhibitory concentration
IMDG-code	International Maritime Code for Dangerous Goods
incl.	including, inclusive
IUCLID	International Uniform Chemical Information Database
LC	lethal concentration
LC50	lethal concentration 50 percent kill
LCLo	lowest published lethal concentration
LD	Lethal Dose of a chemical
LD50	Lethal Dose, 50% kill
LDLo	Lethal Dose Low
LOAEL	Lowest Observed Adverse Effect Level
LOEC	Lowest Observed Effect Concentration
LOEL	Lowest Observed Effect Level
LQ	Limited Quantities
MARPOL	International Convention for the Prevention of Marine Pollution from Ships
n.a.	not applicable
n.av.	not available
n.c.	not checked
n.d.a.	no data available
NIOSH	National Institute of Occupational Safety and Health (United States of America)
NOAEC	No Observed Adverse Effective Concentration
NOAEL	No Observed Adverse Effect Level
NOEC	No Observed Effect Concentration
NOEL	No Observed Effect Level
ODP	Ozone Depletion Potential

Page 12 of 12

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 23.03.2018 / 0014

Replacing version dated / version: 27.09.2016 / 0013

Valid from: 23.03.2018

PDF print date: 28.03.2018

Profi Leichtlauf 10W-40 Basic 60 L

Art.: 7762

OECD Organisation for Economic Co-operation and Development

org. organic

PAH polycyclic aromatic hydrocarbon

PBT persistent, bioaccumulative and toxic

PC Chemical product category

PE Polyethylene

PNEC Predicted No Effect Concentration

POCP Photochemical ozone creation potential

ppm parts per million

PROC Process category

PTFE Polytetrafluorethylene

REACHRegistration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SADT Self-Accelerating Decomposition Temperature

SAR Structure Activity Relationship

SU Sector of use

SVHC Substances of Very High Concern

Tel. Telephone

ThOD Theoretical oxygen demand

TOC Total organic carbon

TRGS Technische Regeln für Gefahrstoffe (=Technical Regulations for Hazardous Substances)

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VbF Verordnung über brennbare Flüssigkeiten (= Regulation for flammable liquids (Austria))

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

WEL-TWA, WEL-STEL WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period), WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period) (EH40, UK).

WHO World Health Organization

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.